



### 电气性能/Electrical

参考标准/Standard	UL	IEC
额定电压/Rated voltage	300V	320V
额定电流/Rated current	10A	15A
接触电阻/Contact resistance	20mΩ	
绝缘电阻/Insulation resistance	5000MΩ/DC1000V	
耐电压/Withstanding voltage	AC 2000V/1 Min	

### 机械性能/Mechanical

温度范围/Temp.Range	-40℃ ~ +105℃
瞬时温度/MAX Soldering	+250℃ for 5 Sec

### 尺寸/Dimensions

间距/Pitch	5.0mm 5.08mm 7.62mm
极数/Poles	2p. xxp

### 材质及电镀/Material

塑件/Housing	PA66,UL94V-0
焊针/Pin header	Brass, Tin plated

#### TOLERANCES EXCEPT AS NOTED

variable range	linear dimension				fillet	chamfer	short angle sid			≡	-	□	//	⊥		
	to 6	to 30	to 120	to 480			to 6	to 10	to 50						to 120	to 5
tolerance	±0.1	±0.2	±0.3	±0.5	±0.2	±0.5	±1	1°	30'	20'	10'	0.5	0.025	0.06	0.12	0.4

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	第一视角/FIRST ANGLE PROJECTION	
慈溪市萬捷電子有限公司						
					名称/NAME	WJ2EDGR-5.0 WJ2EDGR-5.08 WJ2EDGR-7.62